



**Equipos, partes y accesorios de tecnología informática y servicios de soporte técnico**

Cotización No. 001 - 275

NIT	CLIENTE	CONTACTO	FECHA	CIUDAD
			03/10/2016	
TELÉFONO	DIRECCIÓN	EMAIL	DESCUENTO	FORMA DE PAGO

Atendiendo a su amable solicitud, enviamos la cotización de los productos solicitados por su organización:

ITEM	CÓDIGO	DESCRIPCIÓN	CANTIDAD	VR. UNITARIO	VR. TOTAL
1		CAMARAS HD TVI HIKVISION HK-DS2CE16D1T-IT3	1	S/. 449.15	S/. 449.15
2					
3					
4					
5					
6					
<b>Opciones de Pago:</b>				<b>SUBTOTAL</b>	S/. 449.15
				<b>IGV</b>	S/. 80.85
				<b>TOTAL A PAGAR</b>	S/. 530.00

**Codiciones y validez de la oferta:**

30 dias

**Validez:**

**Condiciones de entrega:**

Entrega Inmediata

**Condiciones de Garantía:**

garantia de 1 año

Esperamos haber dado alcance a sus requerimientos

Cordialmente,

RICARDO TALAVERA

RPM: #999033365 RPC:959354677

DIRECCIONES

- Direccion: -Lima: Av Nicolas Arriola 265 Of. 201 (referencia: a 1 cuadra de Cruz del Sur de Javier Prado )

- Calle Rivero 107 of 302. Cercado - Arequipa

También estamos en:

Trujillo Puno Cajamarca - Piura -Tumbes - Ica - Chiclayo - Ayacucho- Tacna - Cusco

CUENTAS BANCARIAS :

INTEGRASAT SOLUCIONES CENTER SRL , RUC : 20455256357

Cuenta Corriente BCP Soles

215-2050250-0-12

Código interbancario: CCI: 00221500205025001225

Cuenta Corriente BCP DOLARES

215-2295979-1-31

Código interbancario: CCI 00221500229597913124

# ESPECIFICACIONES TECNICAS



## DS-2CE16D1T-IT1/IT3 HD1080P Turbo HD EXIR Bullet Camera



**EXIR**



### Key features

- HD1080P Video Output
- Adopt HDTVl Technology
- True Day/Night, Smart IR
- EXIR technology, 20/40m IR distance
- IP66 weatherproof
- OSD menu controlled via UTC

### Dimensions



### Available models

- DS-2CE16D1T-IT1
- DS-2CE16D1T-IT3

	DS-2CE16D1T-IT1	DS-2CE16D1T-IT3
<b>Camera</b>		
Image Sensor	1 / 2.7" Progressive Scan CMOS	
Signal System	PAL / NTSC	
Effective Pixels	1930(H)*1080(V)	
Min. Illumination	0.1 Lux @ (F1.2, AGC ON), 0 Lux with IR	
Shutter speed	1/25(1/30) s to 1/50,000 s	
Lens	3.6mm (6mm optional)	3.6mm (6mm, 8mm, 12mm, 16mm optional)
	Angle of View: 90°(3.6mm), 55.4°(6mm)	Angle of View: 90°(3.6mm), 55.4°(6mm), 41.5°(8mm), 26.5°(12mm), 20.6°(16mm)
Lens Mount	M12	
Angle Adjustment	Pan: 0 - 360°, Tilt: 0 - 90°, Rotation: 0 - 360°	
Day & Night	ICR	
Synchronization	Internal synchronization	
Video Frame Rate	1080p@25fps/1080p@30fps	
HD Video Output	1 Analog HD output	
S / N Ratio	More than 52dB	
<b>Menu</b>		
Camera ID	On/off (0-255)	
AGC	Support	
D/N Mode	Color/ BW/ Auto/ EXT	
White Balance	Auto/ User/ Push/ 8000K/ 6000K/ 4200K/ 3000K	
Privacy Mask	On/Off, maximum 2 zones	
Motion Detection	On/Off, maximum 4 zones	
BLC	Support	
Anti-sticker	On/off	
Language	English/ Chinese	
Function	Digital noise reduction, Mirror	
<b>General</b>		
Working Temperature / Humidity	-40 °C - 60 °C (-40 °F - 140 °F) Humidity 90% or less (non-condensing)	
Power Supply	12 VDC	
Power Consumption	Max. 3W	
Weather Proof Ratings	IP66	
IR Range	Up to 20m	Up to 40m
Communication	Up the coax Protocol: HIKVISION-C/Coaxtron	
Dimensions	86.22*82.05*220.13mm(3.38"*3.23"*8.67")	
Weight	430 g (0.95 lb)	