



Equipos, partes y accesorios de tecnología informática y servicios de soporte técnico

Cotización No. 001 - 182

NIT	CLIENTE	CONTACTO	FECHA	CIUDAD
			24/09/2016	
TELÉFONO	DIRECCIÓN	EMAIL	DESCUENTO	FORMA DE PAGO

Atendiendo a su amable solicitud, enviamos la cotización de los productos solicitados por su organización:

ITEM	CÓDIGO	DESCRIPCIÓN	CANTIDAD	VR. UNITARIO	VR. TOTAL
1		LECTOR DE CODIGO DE BARRAS INALAMBRICO UNITECH MS 380	1	S/. 1,076.27	S/. 1,076.27
2					
3					
4					
5					
6					
Opciones de Pago:				SUBTOTAL	S/. 1,076.27
				IGV	S/. 193.73
				TOTAL A PAGAR	S/. 1,270.00

Codiciones y validez de la oferta:

30 dias

Validez:

Condiciones de entrega:

Entrega Inmediata

Condiciones de Garantía:

garantia de 1 año

Esperamos haber dado alcance a sus requerimientos

Cordialmente,

RICARDO TALAVERA

RPM: #999033365 RPC:959354677

DIRECCIONES

- Direccion: -Lima: Av Nicolas Arriola 265 Of. 201 (referencia: a 1 cuadra de Cruz del Sur de Javier Prado)

- Calle Rivero 107 of 302. Cercado - Arequipa

También estamos en:

Trujillo Puno Cajamarca - Piura -Tumbes - Ica - Chiclayo - Ayacucho- Tacna - Cusco

CUENTAS BANCARIAS :

INTEGRASAT SOLUCIONES CENTER SRL , RUC : 20455256357

Cuenta Corriente BCP Soles

215-2050250-0-12

Código interbancario: CCI: 00221500205025001225

Cuenta Corriente BCP DOLARES

215-2295979-1-31

Código interbancario: CCI 00221500229597913124

ESPECIFICACIONES TECNICAS

unitech

MS380

Rugged Bluetooth Barcode Scanner



A Durable and Versatile Design for Multiple Applications

The MS380's lightweight and ergonomic design is conducive to long hours of scan-intensive operation across various applications. Not only is the CCD scanner designed to feel like an extension of the user's arm, but it is built to withstand the demands of the workplace. The device can absorb multiple 1.2 Meter (4') drops to concrete, and it is sealed with an IP43 rating against the elements. These features help ensure that the MS380 is the ideal bar coding solution for Health Care, Light Industry, Warehouse and Commercial Service applications.

Wireless Connectivity Supports Real-time Data Collection Transactions

The MS380's cradle is equipped with a rotatable antenna that allows the MS380 to roam at least 100 meters in diameter from its access point. The MS380 even alerts users that it is out of this wireless range by vibrating, ensuring that data is captured reliably. In addition, a replaceable battery pack enables the user to operate the device for more than 8 hours without recharging.

Cost-Effective Market Solution

The MS380 offers reliable scanning performance with a read rate of 230 scans per second and a scan width of 200mm. The MS380 also delivers one of the best depth-of-field ranges on the market at 360mm for Bluetooth scanners. This device dependably reads most 1D and GS1 bar codes. The MS380 is a great asset for companies that need a cost-saving data collection solution.

Main Features

- Supports USB HID interface for easy installation
- Supports GS1 codes
- Built-in Bluetooth Class 1
- Rotatable external cradle antenna
- Wireless Coverage: Up to 100 meters (open space)
- ESD protection: 4kv contact/8kv air
- Depth-of-field: 40 - 350mm
- Reading resolution: 4mil
- 1620mAh battery capacity
- 1.2 meter (4') drop threshold



ESPECIFICACIONES TECNICAS

DELTOC

unitech

MS380

Specifications

Operational

Receiving Device	2048 pixel CCD (Charge-coupled device)
Light Source	660nm Visible Red LED
Max. Resolution	4 mil
Scan Rate	230 scans/second
Skew Angle	±30 degree
Pitch Angle	±60 degree
Printing Contrast Scale	60%

Depth of Field

Reading Distance	40-350mm (15 mil EAN) 75-85mm (4 mil Code 39) 70-115mm (5 mil Code 39)
Width of Field	Code 39 : 200mm / 0.9 (40 mil)

Electrical

Battery Type	Lithium-ion
Battery Capacity	1620mAh
Battery Charging time	5 hours
Operating Time	minimum 8 hours

Decoder

Symbologies	UPC-A/UPC/E, EAN-8/EAN-13, Industrial 2 of 5, Codabar, Matrix 2 of 5, Code 11, Code 93, Code 32, Code 128, Standard Code 39, Full ASCII Code 39, Interleaved 2 of 5, China Postal Code, MSI Plessey Code, UK Plessey Code, EAN/UCC 128, Telepen Code, RSS-14, RSS-limited, RSS-Expanded, RSS-Stacked
-------------	--

Environmental

Operating Temperature	0°C to 50°C
Storage Temperature	-10°C to 60°C
Relative Humidity	20% to 85% non-condensing
ESD Protection	4kv contact/8kv air
Mechanical Shock	1.2m onto concrete

Communication

Radio Frequency	2.4GHz Bluetooth, Class 1
Interface Supported	USB (HID)
Range	100M (open space)

BCR Mechanical

Dimensions	L160xW69xH88 mm
Weight	170±10g

AP Cradle

Dimensions	L202xW111xH70
Weight	227±10g
Power	3.45VDC

Regulatory Approvals

FCC Class B, CE, BSMI

Accessory

Adapter, USB cable, Cradle



Unitech America

Los Angeles, Houston, Guadalajara
<http://www.ute.com> e-mail: inquiry@ute.com
<http://latin.unitech-adc.com> e-mail: info@latin.ute.com

Unitech Asia Pacific & Middle East

Taipei
<http://www.unitech-utp.com.tw> e-mail: airdsales@tw.ute.com

Unitech Japan

Tokyo
<http://www.unitech-japan.cn.jp> e-mail: sales@unitech-japan.cn.jp

Unitech Europe

Tilburg / Netherlands
<http://www.unitech-europe.com> e-mail: sales@unitech-europe.com

Unitech Greater China

Beijing, Shanghai, Guang Zhou, Xiamen
<http://www.ute.com.cn> <http://www.ute.cn> unitech@cn.ute.com
Taipei <http://adc-utr.unitech.com.tw> barcode@tw.ute.com

Head Office

Taipei
<http://www.unitech-adc.com> e-mail: marketing@tw.ute.com