



Equipos, partes y accesorios de tecnología informática y servicios de soporte técnico

Cotización No. 001 - 221

NIT	CLIENTE	CONTACTO	FECHA	CIUDAD
			27/09/2016	
TELÉFONO	DIRECCIÓN	EMAIL	DESCUENTO	FORMA DE PAGO

Atendiendo a su amable solicitud, enviamos la cotización de los productos solicitados por su organización:

ITEM	CÓDIGO	DESCRIPCIÓN	CANTIDAD	VR. UNITARIO	VR. TOTAL
1		NVR 4 CANALES HK-DS7104NI-SN	1	S/. 491.53	S/. 491.53
2					
3					
4					
5					
6					
Opciones de Pago:				SUBTOTAL	S/. 491.53
				IGV	S/. 88.47
				TOTAL A PAGAR	S/. 580.00

Codiciones y validez de la oferta:

30 dias

Validez:

Condiciones de entrega:

Entrega Inmediata

Condiciones de Garantía:

garantia de 1 año

Esperamos haber dado alcance a sus requerimientos

Cordialmente,

RICARDO TALAVERA

RPM: #999033365 RPC:959354677

DIRECCIONES

- Direccion: -Lima: Av Nicolas Arriola 265 Of. 201 (referencia: a 1 cuadra de Cruz del Sur de Javier Prado)

- Calle Rivero 107 of 302. Cercado - Arequipa

También estamos en:

Trujillo Puno Cajamarca - Piura -Tumbes - Ica - Chiclayo - Ayacucho- Tacna - Cusco

CUENTAS BANCARIAS :

INTEGRASAT SOLUCIONES CENTER SRL , RUC : 20455256357

Cuenta Corriente BCP Soles

215-2050250-0-12

Código interbancario: CCI: 00221500205025001225

Cuenta Corriente BCP DOLARES

215-2295979-1-31

Código interbancario: CCI 00221500229597913124

ESPECIFICACIONES TECNICAS





DS-7104/08/16NI-SN/P Embedded Mini Plug & Play NVR



Key features

- Third-party network cameras supported
- Up to 2 Megapixels resolution recording
- HDMI and VGA output at up to 1920x1080P resolution
- HDD quota and group management
- 4/8 independent PoE network interfaces are provide

Rear Panel of DS-7104/08/16NI-SN/P



1. Power Supply
2. Audio In
3. HDMI Interface
4. LAN Network Interface
5. Audio Out
6. VGA Interface
7. USB Interface
8. Ground
9. PoE Ethernet Interface

	DS-7104NI-SN/P	DS-7108NI-SN/P	DS-7116NI-SN/P
Video/Audio input			
Video input	4-ch	8-ch	16-ch
Two-way audio input	1-ch, RCA (2.0 Vp-p, 1kΩ)		
Network			
Incoming bandwidth	25Mbps	50Mbps	100Mbps
Outgoing bandwidth	40Mbps		
Remote connection	128		
Video/Audio output			
HDMI/VGA output	1-ch, resolution: 1920 × 1080P /60Hz, 1280 × 1024 /60Hz, 1280 × 720 /60Hz, 1024 × 768 /60Hz		
Audio output	1-ch, RCA (Linear, 1kΩ)		
Decoding			
Live view / Playback resolution	1080P /LXGA /720P /VGA /4CIF /DCIF /2CIF /CIF /QCIF		
Capability	4-ch@720P, 2-ch@1080P	8-ch@4CIF, 4-ch@720P, 2-ch@1080P	8-ch@4CIF, 8-ch@720P, 4-ch@1080P
Hard disk			
SATA	1 SATA interface for 1 HDD		
Capacity	Up to 4TB for each disk		
External interface			
Network interface	1 RJ-45 10 /100 Mbps self-adaptive Ethernet interface		1 RJ-45 10 /100/1000 Mbps self-adaptive Ethernet interface
USB interface	2 × USB 2.0		
PoE			
Interface	4 independent 10 /100 Mbps PoE Ethernet interfaces	8 independent 10 /100 Mbps PoE Ethernet interfaces	
Max. Power	36W	40W	
Supported Standard	AF		
Others			
Power supply	48V DC		
Consumption (without hard disk and PoE)	≤ 6 W	≤ 10 W	≤ 15 W
Working temperature	-10 °C ~ +55 °C (+14 °F ~ +131 °F)		
Working humidity	10 % ~ 90 %		
Chassis	1U chassis		
Dimensions(W × D × H)	255 × 205 × 45 mm	285 × 210 × 45 mm	
Weight	≤ 1 Kg (without hard disk)		