

RUC: 20455256357

COT.
A-01255

SRES :

TEL	RPC / RPM		FECHA	CIUDAD
-	959354677 - #999033365		08-Abr-2017	-
				T. PAGO
				-

[illegible]

ATENTAMENTE
Percy Guerrero
RPM # 999033365 RPC: 959354677

CONDICION DE COMPRA

- Los Precios están expresados en Moneda Soles
- Validez de la Propuesta: 30 días o hasta agotar stock"

GARANTIA DEL PRODUCTO

- GARANTIA DE 2 AÑOS

FORMA DE PAGO

PLAZO DE ENTREGA

- Entrega Inmediata o dentro de 24 a 48 horas

FORMAS DE PAGO

- EN CASO DE ENTIDADES PUBLICAS EL PAGO ES DESPUES DE LA ADQUISICION EN LOS ALMACENES DE LA INSTITUCION

- EN CASO DE EMPRESA PRIVADA

Opcion1: (Envio courier gratis): previo depósito de la totalidad a las cuentas del banco (envio gratis) a la cuenta corriente bcp soles

Opcion2: (Entrega en nuestras oficinas):

Solicitar la direccion mas cercana a su residencia al rpm #999033365 rpc: 959354677, estamos ubicados en - (Distritos de surco, javier prado y wilson) , arequipa, trujillo, otros departamentos

Opcion3: Para Entidades del Estado : Pago despues de la Entrega"

DIRECCIONES

-

Dirección Principal : Av Manuel Olguin 335 - Santiago de Surco

-

Direcciones en Arequipa -Trujillo -Chiclayo -Tacna -Cusco -Moquegua -Cajamrca -Ica -Piura -Tumbes -Loreto

AREQUIPA

Calle Rivero 107 oficina 302g

CUENTAS DEL BANCO

Cuenta Corriente BCP Soles: INTEGRASAT SOLUCIONES CENTER S.R.L

215-2050250-0-12

Cuenta Corriente BCP DOLARES : INTEGRASAT SOLUCIONES CENTER S.R.L

215-2131402-1-39

-

."

TELEFONOS Y RAZON SOCIAL

TELF. -: - TELF. PROVINCIAS : 054-696980

RPM #999033365 RPC: 959354677

RAZON SOCIAL

Razón Social: INTEGRASAT SOLUCIONES CENTER S.R.L

RUC: 20455256357

Multimedia Application with Stunning Sound

ViewSonic
See the difference™ 

PJD5155



3,300 Lumens SVGA with HDMI LightStream Projector

The ViewSonic LightStream PJD5155 projector features 3300 lumens, native SVGA 800 x 600 resolution, and intuitive, user-friendly design. Exclusive SuperColor™ technology offers a wider color range for true-to-life image projection, while SonicExpert™ technology delivers improved sound quality. The PJD5155 also features extensive connectivity including HDMI, 2 x VGA, Composite Video, S-Video, 1 x VGA output, Audio in/out, Mini USB and RS232. An energy-saving DynamicEco® feature reduces power consumption by up to 70%, and extends the lamp life by up to 10,000 hours. With



Multimedia Application with Stunning Sound

PJD5155

Smart Restart/Quick Power Off

With the Smart Restart feature enabled, the projector can be quickly restarted from standby mode without waiting for a power cycle to complete. With the Quick Power Off feature enabled, the projector can be quickly powered off in seconds rather than waiting for a cool-down cycle to complete. This lets users pack the projector away without having to worry about the internal fan still running.



Convenient Auto Power On/Off Feature

All LightStream projectors automatically power on for quick and easy startup whenever a VGA or HDMI cable is connected. Conversely, when no signal is detected from a VGA or HDMI cable, the projector will automatically power off after a user-defined amount of time.



Technical Specifications

Display	Resolution	800x600 (SVGA)
	Lens	Digital Zoom: 0.8X~2.0X
	Size	30 - 300 inch
	Throw Distance	1.0m - 8.0m
	Throw Ratio	1.86~2.04
	Lamp	190W
	Lamp Life	5,000 hours / 6,000 hours (Eco Mode) / 10,000 hours (DynamicEco Mode)
	Brightness	3300 ANSI Lumens
	Contrast Ratio	20,000:1 (DynamicEco Mode)
	Keystone Correction	Vertical: +40~-40°, (Manual)
	Aspect Ratio	4:3
	Color Depth	1.07 Billion Colors (30 bits per color)
	Optical Offset	100%+/-5%
Audio	Speakers	2W cube x 1



Multimedia Application with Stunning Sound



PJD5155

Input Signal	Video	NTSC: NTSC M (3.58 MHz), 4.43MHz PAL: PAL (B, D, G, H, I, M, N, 60) SECAM: SECAM (B, D, G, K, K1, L) SD: 480i and 576i ED: 480p and 576p HD: 720p, 1080i, 1080p
	Frequency	Fh: 15-102KHz; Fv: 23-120Hz
Compatibility	PC	800x600@60Hz (native)
	Mac	800x600@60Hz (native)
Connector	RGB Input	VGA Input x2
	RGB Output	VGA Output x1
	Composite Video	RCA-1 x1
	S Video	Mini-Din 4 pin (x1)
	Component Video	Share with VGA x2
	Digital	HDMI 1.4 x 1
	Audio	3.5mm Mini-Mono Jack (x1)
	USB	Mini USBx1
Power	Voltage	100~240Vac 50/60Hz (Auto Switching)
	Consumption	265 W (Max.)
Operating Conditions	Temperature	0°~40°C / 32°~104°F
	Humidity	10~90%, Non-Condensation
Dimensions	Physical	316mm (width) x 103.7mm (height) x 228mm (depth)
Weight	Net	2.1 kg
Regulations	CB, TUV-GS, UL/cUL, FCC (including ICES-003), CE, C-Tick Mexico Energy test/Registration, EAC, UkrSEPRO/EMC DOC, UL COC, TUV-S Mark(Argentina), PSB, KCC, KC, SASO, CCC WEEE, RoHS, REACH, SVHC, ErP	
Package Contents	1. Power Cord, 1.8m; 2. VGA Cable, 1.8m; 3. Remote Control with Batteries (Without Laser); 4. Quick Start Guide (one sheet version), x1; 5. ViewSonic CD Wizard (w User Manual) x 1	

